



SUBMITTAL/TECHNICAL DATA SHEET

APPLICATION

ABC dry chemical is a multipurpose extinguishing agent that is suitable for use in offices, classrooms, churches, parking garages and retail. Not recommended for use on sensitive electronic equipment.

DESCRIPTIONS

These units contain specially fluidized and siliconized mono ammonium phosphate powder, which smothers and breaks the chain reaction on Class B fires, fuses and insulates Class A fires and is a non-conductor of electricity. Non-toxic.

SPECIFICATIONS

CONFORMS TO TEST STANDARDS:
CAN/ULC-S504 — ANSI/UL299 &
CAN/ULC S508 — ANSI/UL711

OPERATION: Squeeze the lever, which opens the valve, allowing the chemical to be forced out. Upright squeeze grip operation.

TEMPERATURE RANGE: -65° F (-53° C) to 120° F (49° C)

CONSTRUCTION: Heavy-duty steel cylinder with siphon tube, replaceable molded valve stem seal, visual pressure gauge, pull pin and upright squeeze grip. Corrosion and impact resistant powder coat finish.

VALVE MATERIAL: Aluminum

CAPACITY: 2-1/2, 5, 6, 10, 20 lbs

CLASS: A,B,C Fires

SKU: FSE-COSMIC COSMIC EXTINGUISHERS MULTI PURPOSE DRY CHEMICAL



DIMENSIONS AND APPEARANCE

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

STANDARD DIMENSIONS:

Model	Type	Valve	Nominal Capacity	Ship. Weight	Cylinder Dia.	Overall Height	Overall Width	Ship. Vol.	UL Rating @ 68°F	Optional Mount. Bracket
Cosmic 2-1/2E* (FE02C)	ABC Dry Chemical	Aluminum	2-½ lbs.	5-½ lbs.	3-¾"	15-½"	5-¾"	.2 cu.ft.	1A-10B:C	MB817C*
Cosmic 5E (FE05C)			5 lbs.	10 lbs.	4-¼"	16-¾"	7-¾"	.35 cu.ft.	3A-40B:C	MB818C
Cosmic 5B* (FE05BC)			5 lbs.	10 lbs.	4-¼"	16-¾"	7-¾"	.35 cu.ft.	3A-40B:C	MB818C*
Cosmic 10E (FE10C)			10 lbs.	18-¼" lbs.	5-½"	21"	7-¾"	.65 cu.ft.	4A-80B:C	MB846C
Cosmic 20E (FE20C)			20 lbs.	33-½ lbs.	7-½"	21-¼"	8-¾"	1.0 cu.ft.	10A-120B:C	MB811C
Cosmic 5E (FE05CBV)		Brass	5 lbs.	10 lbs.	4-¼"	16-¾"	7-¾"	.35 cu.ft.	3A-40B:C	MB818C
Cosmic 10E (FE10CBV)			10 lbs.	18-¼" lbs.	5-½"	21"	7-¾"	.65 cu.ft.	4A-80B:C	MB846C
Cosmic 20E (FE20CBV)			20 lbs.	33-½ lbs.	7-½"	21-¼"	8-¾"	1.0 cu.ft.	10A-120B:C	MB811C

*Indicates mounting bracket standard. J hook wall bracket standard with all other extinguisher

- mounting bracket available for those models at extra charge.

- These all products are USCG approved.

Note: NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.



CLASS A FIRES
Common
Combustibles



CLASS B FIRES
Flammable
Liquids and Gases



CLASS C FIRES
Energized
Electrical Equipment

For a complete list of options visit
www.FireSafetyEquipment.com

PROJECT DATA

Custom Sizes Available - Fast!

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :				
TAGGING INSTRUCTIONS :	SUBMITTAL APPROVAL : (signature or stamp)			

Scan  or 



To view Pricing and
Additional Product Info.



TELEPHONE:
1-888-441-4469
FAX:
1-888-828-6021



PO BOX 7775 PMB 76520,
SAN FRANCISCO,
CALIFORNIA 94120-7775
US



WEBSITE:
www.FireSafetyEquipment.com
E-MAIL:
info@FireSafetyEquipment.com