



SUBMITTAL/TECHNICAL DATA SHEET

APPLICATION

The Water extinguisher uses ordinary water as it's extinguishing agent, and can be pressurized with regular air, making recharging the extinguisher simple and economical.

DESCRIPTIONS

Pressurized Water Extinguishers for Class "A" Fires

The "water press" extinguisher contains water and compressed air. Units shipped empty.

SPECIFICATIONS

CONFORMS TO TEST STANDARDS:
CAN/ULC-S507-ANSI/UL626 &
CAN/ULC S508-ANSI/UL711

OPERATION: Squeeze the lever, which opens the valve, allowing the water to be forced out. Upright squeeze grip operation.

TEMPERATURE RANGE: 40° F (4° C) to 120° F (49° C)

CONSTRUCTION: Butt-welded 304-L stainless steel cylinder (eliminates all internal and external crevices). Rugged stainless steel discharge lever and fixed carry handle with visual pressure gauge, pull pin. All-metal valve body with replaceable molded valve stem seal. UL labeled chemical engine hose.

NOMINAL CAPACITY: 2.5 Gallons

UL Rating: 2A

CLASS: A Fires

SKU: **FSE-GRENADIER**

GRENADIER EXTINGUISHERS


PRESSURIZED WATER



DIMENSIONS AND APPEARANCE

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

STANDARD DIMENSIONS:

Model	Type	Nominal Capacity	Ship. Weight	Cylinder Dia.	Overall Height	Overall Width	Shipping Vol	UL Rating 	Optional Mount. Bracket
Grenadier-P (FP02C)	Water	2-½ gal.	8.3 lbs.	7"	24-½"	9"	1.1 cu.ft.	2A	MB810C

J Hook wall bracket standard - Mounting bracket available at extra charge.

- The Grenadier Extinguisher is shipped empty.

- These all products are USCG approved.

Note: NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.



CLASS B FIRES

Common
Combustibles

For a complete list of options visit
www.FireSafetyEquipment.com

PROJECT DATA

Custom Sizes Available - Fast!

Scan  or  Click



To view Pricing and
Additional Product Info.

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :				
TAGGING INSTRUCTIONS :	SUBMITTAL APPROVAL : (signature or stamp)			



TELEPHONE:
1-888-441-4469
FAX:
1-888-828-6021



PO BOX 7775 PMB 76520,
SAN FRANCISCO,
CALIFORNIA 94120-7775
US



WEBSITE:
www.FireSafetyEquipment.com
E-MAIL:
info@FireSafetyEquipment.com