



# SUBMITTAL/TECHNICAL DATA SHEET

## APPLICATIONS

Class K extinguishers are extremely effective in suppressing high temperature fires involving cooking oils and grease. The unique cooling properties deliver exceptional heat absorption ensuring the fire remains out.

## DESCRIPTIONS

These units are ideal for commercial restaurant applications as a portable supplement to pre-engineered suppression systems. A low "pH" potassium acetate and potassium citrate solution is discharged in a fine mist that provides excellent range while cooling the fire and preventing splashing of liquid cooking media fires.

## SPECIFICATIONS

CONFORMS TO TEST STANDARDS: :  
CAN/ULC-S554-ANSI/UL8 &  
CAN/ULC-S508-ANSI/UL711

OPERATION: Squeeze the lever, which opens the valve, allowing the chemical to be forced out.

TEMPERATURE RANGE: 40° F (4° C) to 120° F (49° C)

CONSTRUCTION: Stainless steel cylinder with protective nozzle tip orifice seal and non-metallic nozzle tip finger guard. Industry standard horn and nozzle design. Name plate shows only the class "K" symbol.

SKU: **FSE-SATURN**

## SATURN EXTINGUISHER

CLASS K WET CHEMICAL



## DIMENSIONS AND APPEARANCE

>> [CLICK TO VIEW ADDITIONAL DETAILS AND PRICING](#) <<

### STANDARD DIMENSIONS:

Model	Type	Nominal Capacity	Ship. Weight	Cylinder Dia.	Overall Height	Overall Width	Shipping Vol	UL Rating @ 68°F	Optional Mount. Bracket
Saturn 15 (FK15C)	Class K Wet Chemical	6 lbs.	22.75 lbs.	7"	19-1/4"	9"	.9 cu.ft.	1-A:K	MB810C
Saturn 25 (FK25C)		2.5 lbs.	30 lbs.	7"	24-1/2"	9"	1.1 cu.ft.	1-A:K	MB810C

J Hook wall bracket standard - Mounting bracket available at extra charge.

All units meet the current requirements established by the National Fire Protection Association (NFPA) for NFPA10 "Standard for Portable Fire Extinguishers", and any other applicable NFPA standards. Tested and listed by UL to meet construction and performance standards for this type of extinguisher, and can be used where required by local codes such as OSHA.

**Note:** NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.





### CLASS K FIRES

Cooking Oils,  
Greases,  
and Fats

For a complete list of options visit [www.FireSafetyEquipment.com](http://www.FireSafetyEquipment.com)

## PROJECT DATA

**Custom Sizes Available - Fast!**

Scan  or  Click



To view Pricing and Additional Product Info.

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :				
TAGGING INSTRUCTIONS :	SUBMITTAL APPROVAL : (signature or stamp)			



TELEPHONE:  
1-888-441-4469  
FAX:  
1-888-828-6021



PO BOX 7775 PMB 76520,  
SAN FRANCISCO,  
CALIFORNIA 94120-7775  
US



WEBSITE:  
[www.FireSafetyEquipment.com](http://www.FireSafetyEquipment.com)  
E-MAIL:  
[info@FireSafetyEquipment.com](mailto:info@FireSafetyEquipment.com)